

# CHASE International Exports Ltd.

## CERTIFICATE OF QUALITY

Product : 600N

Property	Test Method	Guarantee Spec.	Test Result	Unit
APPEARANCE	ASTM D4176	PASS(C&B)	PASS(C&B)	
API,Gravity @60°F	ASTM D4052	To be reported	31.5	
DENSITY, @15°C, kg/L	ASTM D4052	To be reported	0.8654	kg/L
DENSITY, @25°C, g/cm <sup>3</sup>	ASTM D4052		0.8607	g/cm <sup>3</sup>
ACIDITY TOTAL	ASTM D974	0.01 Max	0.003	mgKOH/g
ANILINE POINT, °C	ASTM D611	To be reported	128.4	°C
Carbon Conradson, wt%	ASTM D189	0.01 Max	L0.01	wt%
COLOR ASTM	ASTM D1500	0.5 Max	L0.5	
COLOR SAYBOLT	ASTM D156	30 Min	+30	
Cu-strip (100°C, 3h)	ASTM D130	1 Max	1A	
VISCOS. KIN. @40°C, mm <sup>2</sup> /s	ASTM D445	To be reported	104.3	mm <sup>2</sup> /s
VISCOS. KIN. @100°C, mm <sup>2</sup> /s	ASTM D445	12 ~ 12.9	12.05	mm <sup>2</sup> /s
VISCOSITY INDEX	ASTM D2270	95 Min	105	
POUR POINT, °C	ASTM D6749	-13 Max	-14	°C
FLASH POINT, COC, °C	ASTM D92	246 Min	268	°C
SULFUR, wtppm	ASTM D5453	10 Max	2	wtppm
MOISTURE CONTENT, wtppm	ASTM D6304	100 Max	32.9	wtppm
CA, %	ASTM D3238	1 Max	0.0	%

CHASE INTERNATIONAL EXPORTS LTD.

  
Authorized Signature

**OFFICE**

62 MODY ROAD,  
503, WING ON PLAZA  
TST-EAST, KOWLOON,  
HONG KONG.

**TELEPHONE / FAX**

TEL: 852-2723 3467 (5 LINES)  
FAX: 852-2721 9464

**E-MAIL ADDRESS**

chaseint@netvigator.com

**MAILING ADDRESS**

T.S.T.P.O. BOX 91310  
KOWLOON,  
HONG KONG.